

FISO Metal Building Series

Knock Down and Preassembled Door Systems





FMB-KD – Metal Building Knock Down System

System Features:

- 12 gauge adjustable girt clips for easy installation
- 18 gauge galvanneal door with polyurethane or polystyrene core
- Kerf weather seal
- 18 gauge galvanneal frame with 7 gauge hinge reinforcements
- 161 cylindrical lock prep
- Choice of 1 or Grade 2 cylindrical lockGrade
- Powder coated Ball Bearing NRP Hinges
- Sill Plate and Threshold
- Standard color is Tru White other color options available


FISO's standard powder coated paint provides the industry's most durable finish. Ask your representative about FISO's extended finish warranty.

Frame Order & Options

☐ BRONZE	3070	4 1/4	NO LOCK	OPT
☐ WHITE	4070	5 3/4	STD. LOCK	
PRIME	8070	6 1/4	LEVER LOCK	
		8 1/4	DBL. LOCK	
		10 1/4	ADA	








FMB Series utilizes a kerf weatherstripping that conforms to the fit of the door, finishes for a tight seal with low air infiltration and is tear resistant. FISO Knock Down Door Systems offer you, the building manufacturer, the greatest degree of design flexibility. These reversible (non-handed) units install quickly and eliminate costly handing error.

Prime Options:



FDA-compliant Grey FDA - 09/70339 gloss level 85±5



FDA-compliant White FDA - 09/10126 gloss level 90+

Typical Hardware Options














INTERIOR





EXTERIOR

- A / LHR / LHO = Outswing left hand reverse
- B / RHR / RHO = Outswing right hand reverse
- C / LHRA / LHOA = Outswing left hand reverse active
- D / RHRA / RHOA = Outswing right hand reverse active
- AI / LH / LHI = Inswing left hand
- BI / RH / RHI = Inswing right hand
- CI / LHA / LHAI = Inswing left hand active
- DI / RHA / RHAI = Inswing right hand active
- E / BHRA / BHO = Outswing both hands reverse active